



BARGE "GONSOULIN - 120"

LE BEOUF BROTHERS

HULL NO. 4399

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(-) 0' - 0 7/8"	(-) 0' - 1"	(+) 0' - 0 7/8"
1'-0"	(-) 0' - 1 3/4"	(-) 0' - 2"	(+) 0' - 1 3/4"
1'-6"	(-) 0' - 2 3/4"	(-) 0' - 3 1/8"	(+) 0' - 2 5/8"
2'-0"	(-) 0' - 3 5/8"	(-) 0' - 4 1/8"	(+) 0' - 3 1/2"
2'-6"	(-) 0' - 4 1/2"	(-) 0' - 5 1/8"	(+) 0' - 4 3/8"
3'-0"	(-) 0' - 5 3/8"	(-) 0' - 6 1/8"	(+) 0' - 5 1/8"
3'-6"	(-) 0' - 6 1/4"	(-) 0' - 7 1/8"	(+) 0' - 6"
4'-0"	(-) 0' - 7 1/4"	(-) 0' - 8 1/8"	(+) 0' - 6 7/8"
4'-6"	(-) 0' - 8 1/8"	(-) 0' - 9 1/4"	(+) 0' - 7 3/4"
5'-0"	(-) 0' - 9"	(-) 0' - 10 1/4"	(+) 0' - 8 5/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 1/28/02

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "GONSOULIN - 120"
LE BEOUF BROTHERS

OUTAGE TABLE

1 PORT OR STAR.

HULL NO. 4399

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for gauge height (0 FT. to 16 FT.) and corresponding capacity values. The table is organized into 16-foot intervals, with each interval containing 16 individual gauge readings and their respective capacities. The capacity values generally increase as the gauge height increases, with some fluctuations.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 1/28/02


* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-3 1/4" (RIM OF HATCH
LOCATED ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature

INSPECTORATE AMERICA CORPORATION



BARGE "GONSOULIN - 120" LE BEOUF BROTHERS

OUTAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

3 PORT OR STAR.

HULL NO. 4399

Table with columns for gauge height (0 FT. to 16 FT.) and corresponding capacity values in gallons. Includes a note 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' at the bottom.

INSPECTORATE ISO 9002 ACCREDITED

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-8" (RIM OF HATCH LOCATED ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature

INSPECTORATE AMERICA CORPORATION

STRAPPED: 1/10/02



BARGE "GONSOU LIN - 120" LE BEOUF BROTHERS

INNAGE TABLE

1 PORT OR STAR

HULL NO. 4389

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

IN	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	
0	0	283.88	0	970.92	0	1,662.46	0	2,008.21	0	3,045.44	0	3,391.18	0	4,082.67	0	4,428.42
1/4	0.34	291.08	1/4	978.12	1/4	1,669.67	1/4	2,015.41	1/4	3,052.64	1/4	3,398.39	1/4	4,089.87	1/4	4,435.62
1/2	1.04	639.49	1/2	985.33	1/2	1,676.87	1/2	2,022.61	1/2	3,059.85	1/2	3,405.59	1/2	4,097.08	1/2	4,442.82
3/4	2.14	646.69	3/4	992.53	3/4	1,684.07	3/4	2,029.82	3/4	3,067.05	3/4	3,412.79	3/4	4,104.28	3/4	4,450.03
1	3.94	653.90	1	999.74	1	1,691.28	1	2,037.02	1	3,074.25	1	3,420.00	1	4,111.48	1	4,457.23
1/4	6.64	661.10	1/4	1,006.94	1/4	1,352.74	1/4	2,044.22	1/4	3,081.45	1/4	3,427.20	1/4	4,118.69	1/4	4,464.43
1/2	9.34	668.31	1/2	1,014.15	1/2	1,359.94	1/2	2,051.43	1/2	3,088.66	1/2	3,434.40	1/2	4,125.89	1/2	4,471.63
3/4	12.04	675.51	3/4	1,021.35	3/4	1,367.14	3/4	2,058.63	3/4	3,095.86	3/4	3,441.60	3/4	4,133.09	3/4	4,478.84
2	14.74	682.72	2	1,028.56	2	1,374.34	2	2,065.83	2	3,103.06	2	3,448.81	2	4,140.30	2	4,486.04
1/4	19.24	689.92	1/4	1,035.76	1/4	1,381.55	1/4	2,073.04	1/4	3,110.27	1/4	3,456.01	1/4	4,147.50	1/4	4,493.24
1/2	23.74	697.13	1/2	1,042.97	1/2	1,388.75	1/2	2,080.24	1/2	3,117.47	1/2	3,463.21	1/2	4,154.70	1/2	4,500.45
3/4	28.24	704.33	3/4	1,050.17	3/4	1,395.95	3/4	2,087.44	3/4	3,124.67	3/4	3,470.42	3/4	4,161.91	3/4	4,507.65
3	32.74	711.54	3	1,057.38	3	1,403.16	3	2,094.64	3	3,131.88	3	3,477.62	3	4,169.11	3	4,514.85
1/4	39.05	718.74	1/4	1,064.58	1/4	1,410.36	1/4	2,101.85	1/4	3,139.08	1/4	3,484.82	1/4	4,176.31	1/4	4,522.06
1/2	45.35	725.95	1/2	1,071.79	1/2	1,417.56	1/2	2,109.05	1/2	3,146.28	1/2	3,492.03	1/2	4,183.51	1/2	4,529.26
3/4	51.65	733.15	3/4	1,078.99	3/4	1,424.77	3/4	2,116.25	3/4	3,153.48	3/4	3,499.23	3/4	4,190.72	3/4	4,536.46
4	57.96	740.36	4	1,086.20	4	1,431.97	4	2,123.46	4	3,160.69	4	3,506.43	4	4,197.92	4	4,543.66
1/4	64.87	747.56	1/4	1,093.40	1/4	1,439.17	1/4	2,130.66	1/4	3,167.89	1/4	3,513.63	1/4	4,205.12	1/4	4,550.86
1/2	71.79	754.77	1/2	1,100.61	1/2	1,446.37	1/2	2,137.86	1/2	3,175.09	1/2	3,520.84	1/2	4,212.33	1/2	4,558.07
3/4	78.70	761.97	3/4	1,107.81	3/4	1,453.58	3/4	2,145.07	3/4	3,182.30	3/4	3,528.04	3/4	4,219.53	3/4	4,565.27
5	85.62	769.18	5	1,115.02	5	1,460.78	5	2,152.27	5	3,189.50	5	3,535.24	5	4,226.73	5	4,572.48
1/4	92.53	776.38	1/4	1,122.22	1/4	1,467.98	1/4	2,159.47	1/4	3,196.70	1/4	3,542.45	1/4	4,233.94	1/4	4,579.68
1/2	99.45	783.59	1/2	1,129.43	1/2	1,475.19	1/2	2,166.67	1/2	3,203.91	1/2	3,549.65	1/2	4,241.14	1/2	4,586.88
3/4	106.36	790.79	3/4	1,136.63	3/4	1,482.39	3/4	2,173.88	3/4	3,211.11	3/4	3,556.85	3/4	4,248.34	3/4	4,594.09
6	113.28	798.00	6	1,143.84	6	1,489.59	6	2,181.08	6	3,218.31	6	3,564.06	6	4,255.54	6	4,601.29
1/4	120.19	805.20	1/4	1,151.04	1/4	1,496.80	1/4	2,188.28	1/4	3,225.51	1/4	3,571.26	1/4	4,262.75	1/4	4,608.49
1/2	127.11	812.41	1/2	1,158.25	1/2	1,504.00	1/2	2,195.49	1/2	3,232.72	1/2	3,578.46	1/2	4,269.95	1/2	4,615.69
3/4	134.02	819.61	3/4	1,165.45	3/4	1,511.20	3/4	2,202.69	3/4	3,239.92	3/4	3,585.66	3/4	4,277.15	3/4	4,622.90
7	140.94	826.82	7	1,172.66	7	1,518.40	7	2,209.89	7	3,247.12	7	3,592.87	7	4,284.36	7	4,630.10
1/4	147.85	834.02	1/4	1,179.86	1/4	1,525.61	1/4	2,217.10	1/4	3,254.33	1/4	3,600.07	1/4	4,291.56	1/4	4,637.30
1/2	154.77	841.23	1/2	1,187.07	1/2	1,532.81	1/2	2,224.30	1/2	3,261.53	1/2	3,607.27	1/2	4,298.76	1/2	4,644.51
3/4	161.68	848.43	3/4	1,194.27	3/4	1,540.01	3/4	2,231.50	3/4	3,268.73	3/4	3,614.48	3/4	4,305.97	3/4	4,651.71
8	168.60	855.64	8	1,201.47	8	1,547.22	8	2,238.70	8	3,275.94	8	3,621.68	8	4,313.17	8	4,658.91
1/4	175.80	862.84	1/4	1,208.68	1/4	1,554.42	1/4	2,245.91	1/4	3,283.14	1/4	3,628.88	1/4	4,320.37	1/4	4,666.12
1/2	183.01	870.05	1/2	1,215.88	1/2	1,561.62	1/2	2,253.11	1/2	3,290.34	1/2	3,636.09	1/2	4,327.57	1/2	4,673.32
3/4	190.21	877.25	3/4	1,223.08	3/4	1,568.83	3/4	2,260.31	3/4	3,297.54	3/4	3,643.29	3/4	4,334.78	3/4	4,680.52
9	197.42	884.46	9	1,230.28	9	1,576.03	9	2,267.52	9	3,304.75	9	3,650.49	9	4,341.98	9	4,687.72
1/4	204.62	891.66	1/4	1,237.49	1/4	1,583.23	1/4	2,274.72	1/4	3,311.95	1/4	3,657.69	1/4	4,349.18	1/4	4,694.93
1/2	211.83	898.87	1/2	1,244.69	1/2	1,590.43	1/2	2,281.92	1/2	3,319.15	1/2	3,664.90	1/2	4,356.38	1/2	4,702.13
3/4	219.03	906.07	3/4	1,251.89	3/4	1,597.64	3/4	2,289.13	3/4	3,326.36	3/4	3,672.10	3/4	4,363.59	3/4	4,709.33
10	226.24	913.28	10	1,259.10	10	1,604.84	10	2,296.33	10	3,333.56	10	3,679.30	10	4,370.79	10	4,716.54
1/4	233.44	920.48	1/4	1,266.30	1/4	1,612.04	1/4	2,303.53	1/4	3,340.76	1/4	3,686.51	1/4	4,378.00	1/4	4,723.74
1/2	240.65	927.69	1/2	1,273.50	1/2	1,619.25	1/2	2,310.73	1/2	3,347.97	1/2	3,693.71	1/2	4,385.20	1/2	4,730.94
3/4	247.85	934.89	3/4	1,280.71	3/4	1,626.45	3/4	2,317.94	3/4	3,355.17	3/4	3,700.91	3/4	4,392.40	3/4	4,738.15
11	255.06	942.10	11	1,287.91	11	1,633.65	11	2,325.14	11	3,362.37	11	3,708.12	11	4,399.60	11	4,745.35
1/4	262.26	949.30	1/4	1,295.11	1/4	1,640.86	1/4	2,332.34	1/4	3,369.57	1/4	3,715.32	1/4	4,406.81	1/4	4,752.55
1/2	269.47	956.51	1/2	1,302.31	1/2	1,648.06	1/2	2,339.55	1/2	3,376.78	1/2	3,722.52	1/2	4,414.01	1/2	4,759.75
3/4	276.67	963.71	3/4	1,309.52	3/4	1,655.26	3/4	2,346.75	3/4	3,383.98	3/4	3,729.72	3/4	4,421.21	3/4	4,766.96

STRAPPED: 1/28/02

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT
REFERENCE GAUGE HEIGHT: 16'-8 1/4" (RIM OF HATCH
LOCATED ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "GONSOULIN - 120" LE BEOUF BROTHERS

INNAGE TABLE

2 PORT OR STAR

HULL NO. 4399

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with 26 columns (0 FT. to 14 FT.) and multiple rows of capacity and gauge data for various barge sections.

STRAPPED: 1/28/02

REFERENCE GAUGE HEIGHT: 16'-8 1/4" (RIM OF HATCH LOCATED ON EXPANSION TRUNK)

* CAPACITY BELOW STRIKE POINT

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "GONSOU LIN - 120" LE BEOUF BROTHERS

INNAGE TABLE

3 PORT OR STAR

HULL NO. 4399

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Main data table with columns for height (0 FT. to 14 FT.) and capacity. Includes a 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' section at the bottom.

STRAPPED: 1/28002

REFERENCE GAUGE HEIGHT: 16'-8" (RIM OF HATCH LOCATED ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and title: INSPECTORATE AMERICA CORPORATION