



BARGE "GONSOULIN - 125"
LE BEOUF BROTHERS

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2146-3

Table with columns for gauge height (0 FT. to 14 FT.) and rows for depth increments (0, 1/4, 1/2, 3/4). Each cell contains capacity values for different barge configurations.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/27/05

PORT REFERENCE GAUGE HEIGHT : 16'-7" (RIM OF HATCH ON EXPANSION TRUNK)

STAR REFERENCE GAUGE HEIGHT : 16'-7 1/2" (RIM OF HATCH ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature
INSPECTORATE AMERICA CORPORATION

BARGE "GONSOU LIN - 125"
LE BEOUF BROTHERS

OUTAGE TABLE

1 PORT OR STAR



BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2146-3

Table with 17 columns (1 FT. to 16 FT.) and 17 rows (0 to 11). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/27/05

REFERENCE GAUGE HEIGHT : 16'-7 1/4" (RIM OF HATCH ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION

BARGE "GONSOULIN - 125"
LE BEOUF BROTHERS

OUTAGE TABLE

2 STAR



BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2146-3

Table with 17 columns (1 FT. to 16 FT.) and multiple rows (0 to 11) showing capacity data in barrels of 42 U.S. gallons. Each cell contains a value and a gauge height fraction (e.g., 0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/27/05

REFERENCE GAUGE HEIGHT : 16'-7" (RIM OF HATCH ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature
INSPECTORATE AMERICA CORPORATION

**BARGE "GONSOULIN - 125"
LE BEOUF BROTHERS**

OUTGAGE TABLE

3 PORT



BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2146-3

Table with 16 columns (1 FT. to 16 FT.) and 3 rows per column (0, 1/4, 1/2, 3/4). Each cell contains capacity values in barrels. A diagonal line is drawn through the table from the top-left to the bottom-right.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/27/05

REFERENCE GAUGE HEIGHT : 16'-7" (RIM OF HATCH ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature

INSPECTORATE AMERICA CORPORATION



BARGE "GONSOULIN - 125"
LE BEOUF BROTHERS

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2146-3

Table with 17 columns (1 FT. to 16 FT.) and multiple rows of capacity data. Includes a 'SUMP 0.34' label near the 15 FT. column.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/27/05

REFERENCE GAUGE HEIGHT: 16'-7 1/2" (RIM OF HATCH ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "GONSOULIN - 125"

LE BEOUF BROTHERS

HULL NO. 2146-3

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(-) 0' - 0 7/8"	(-) 0' - 1"	(+) 0' - 0 7/8"
1'-0"	(-) 0' - 1 3/4"	(-) 0' - 2"	(+) 0' - 1 3/4"
1'-6"	(-) 0' - 2 3/4"	(-) 0' - 3 1/8"	(+) 0' - 2 5/8"
2'-0"	(-) 0' - 3 5/8"	(-) 0' - 4 1/8"	(+) 0' - 3 1/2"
2'-6"	(-) 0' - 4 1/2"	(-) 0' - 5 1/8"	(+) 0' - 4 3/8"
3'-0"	(-) 0' - 5 3/8"	(-) 0' - 6 1/8"	(+) 0' - 5 1/8"
3'-6"	(-) 0' - 6 1/4"	(-) 0' - 7 1/8"	(+) 0' - 6"
4'-0"	(-) 0' - 7 1/4"	(-) 0' - 8 1/8"	(+) 0' - 6 7/8"
4'-6"	(-) 0' - 8 1/8"	(-) 0' - 9 1/4"	(+) 0' - 7 3/4"
5'-0"	(-) 0' - 9"	(-) 0' - 10 1/4"	(+) 0' - 8 5/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 12/27/05 BY: *ASaur*
INSPECTORATE AMERICA CORPORATION